

CAN-50
Mobile Aircraft Fuel Tank
Ventilating System



Pneumatic Driven 8 inch Duct/Fuel Ventilation System with dual APV-2 Ventilators. A highly adaptive and portable system to ventilate one or more Aircraft Fuel Tanks at once. All equipment stores within a tough, reusable container. Provides a smaller footprint for Mobility/Deployment conditions. Achieves an unparalleled level of safety and efficiency. Operates in a wide range of set-up configurations applied to any size of aircraft. Functions with portable or stationary compressed air supply. Proven to drastically reduce the time required to render fuel tank(s) safe for inspection or repair.

SYSTEM CONTENTS

- 2 ea - Pneumatic Driven Air Movers, **APV-2**
- 8 ea - 8 in. Dia. X 20 ft. Conductive Ducting, **NFRA-820X**
- 4 ea - 4 in. Dia. X 15 ft. Conductive Ducting, **NFRA-4X**
- Multiple Port Air Duct Adapter
- 2 ea - Inlet Compressed Air Hose Assembly
- Intake Air Filter Adapter
- Rollable Equipment Storage Cart



SPECIFICATIONS

Classification:	Dual Pneumatic Driven Air Mover System with Ducting, Storage Cart
Compressed Air Supply Requirements:	Pressure: 80 psi (5.5 bar)
Air Filtration:	Input
Ventilator Air Flow Displacement:	1500 cfm (2549 m³/hr) per Ventilator
Max. Ducting Size:	8 inch Diameter Conductive
National Stock Number:	NSN 4720-01-562-4911

PART #	DESCRIPTION
CAN-50	Rhine Air Mobile Aircraft Fuel Tank Ventilating System

Berry Compliant and Made In U.S.A.